Chapter 7: Supplier **Contact Information**



| Supplier | Product | Primary Contact Information | | |
|----------------------------|--|--|--|--|
| Pattison Sign | Primary Sign | Norm Fry 555 Ellesmere Road Toronto, ON. M1R 4E8 Tel.: 416.701.4596 | nfry@pattisonsign.com www.pattisonsign.com | |
| Sobotec | White Frames | Melissa Almeida 67 Burford Rd. Hamilton, ON L8E 3C6 (905) 578-1278 Ext. 305 | malmeida@sobotec.com www.sobotec.com | |
| Plan B | Furniture | David Muller 380 King Street East Toronto, On. M5A 1K9 | Tel.: 416.941.10.10 Toll free: 1.866.657.5262 davidm@planboffice.com www.planboffice.com | |
| Savoia Canada / Division 9 | Showroom Tiles, Wood-look ceramic tiles. | Anthony Ondretti 145 King Street East, Toronto, On. M5C 1G6 | Mobile: 416.417.3166 Toll free: 1.800.668.1537 AOndretti@savoia.com www.savoia.com | |
| Olympia Stone + Tile | Showroom Tile, Wood-look Tile, and Concrete-look Tile | Gadi Sonderling 1000 Lawrence Ave West, Toronto ON M6A-1C6 www.olympiatile.com | Tel: 416 785-2509 Fax: 416 789-5745 gadi@olympiatile.com | |
| Centura Tile | Showroom Tiles | Kris George Tel.: 416.525.8628 kgeorge@centura.ca www.centura.ca | +1.514.858.6556 toll free +1.877.999.8990 | |
| Centural Tile (Montreal) | Showroom Tiles | Mima Soares Architectural Sales Manager Tel.: 514.336.4311 msoares@centura.info | | |
| Argelith Ceramic Tiles | Shop and Drive Through Flooring | Christian Nierenkoether 40W310 LaFox Road., Suite F2 St Charles, IL, 60175 | Tel.: 630.444.0665 Mobile: 630.746.9668 christian@argelithusa.com www.argelithusa.com | |
| Stone Tile | Wood-look Tile | Sandra Ng Tel: 416.515.9000 ext. 231 sandra@stone-tile.com www.stone-tile.com | | |
| Roca Tile USA | Showroom Tile, Wood-look and Concrete-look tiles | Cristina Dordas cristina.dordas@rocatileusa. com | Tel: 312-513-8158 | |

 $^{^{*}}$ Please copy Weis & Associates on all communications for best possible assistance and guidance



| Supplier Product | | Primary Contact Information | | | |
|-------------------------------|---|--|---|--|--|
| Tandus Centiva | Second Floor Carpets | Kurt Gibbons Account Executive 2820 Argentia Rd, Mississauga, On. L5N 8G4 | Mobile: 416.254.3324 kurt.gibbons@tarkett.com | | |
| Safeguard Marketing Solutions | Interior Graphics, Secondary Signage, Welcome Wall | Mike Gommerman Toll free: 1.866.313.0039 Mobile: 905.467.4528 | mike@brandwithsms.com www.brandwithsms.com | | |
| Snap On Equipment Solutions | Workshop Equipment | Jamie Boudreau 6500 Millcreek Dr, Mississauga, ON L5N 2W6 | Tel.: 416-254-3169 jamie.boudreau@snapon.com | | |
| Mercury Lighting | General Lighting | Sabine M. Blasl Lighting Specialist | Office: 905-738-6161 Cell: (647) 226-8824 Sabine.susman@gmail.com | | |
| Optecha Lighting | Showroom RGB lights / General Lighting | Rudy Ponce 57 Mill Street North, Suite 204 Brampton, On. L6X 1S9 | Tel.: 647.922.LITE(5483) Mobile: 416.356.7839 rponce@optecha.com www.optecha.com | | |
| Media Graph - TLS | Showroom RGB Lights | David Sellam dudi@tls-led.com dudi@media-graph.com +1.514.858.6556 | Amanda Werbin amansaw@tls-led.com +1.514.858.6556 toll free +1.877.999.8990 | | |
| Sistemalux - Iguzzini | Showroom RGB Lights | Andrew Kedziesdki andrew@sistemalux.com T +1 (416) 408 3995 # 124 M 416-837-0092 | Sistemalux Toronto Office 179 John St, Suite #101 M5T 1X4 | | |
| Richporter Lighting | General Lighting | Paulina Munoz email: paulina.munoz@ richporterlighting.com T. +1.514.395.3795 ext. 222 SF. +1.877.885.6945 3550 43e Avenue Montréal, Québec - H1A 3A7 Canada | Francois Lahaie email: francois@richporterlighting. com | | |
| NRG | Showroom RGB Lights | Hugo Lajeunesse hlajeunesse@nrgqc.com T: +1 (450) 623 1666 ext.108 M: 514 999 8122 | www.nrgqc.com 293, Boul. Industriel St-Eustache, Québec J7R 6B7 Toll-free: 1-877-694-4562 | | |

 $^{^{*}}$ Please copy Weis & Associates on all communications for best possible assistance and guidance



Chapter 8: Material Specifications



8.1 Supplier Lead Times

| Supplier | ltem | Action | Initiate Contact | Order Lead Time |
|--|--|--|------------------------------|--|
| Pattison Sign Group | Primary Sign | Coordinate: Volkswagen clips for Entry Frame Brand Pylon Exterior directional signs Dealer name element (project specific) Sign permitting Sign installation | DCD Stage | 15 weeks (May vary depending on municipal approvals) |
| Sobotec | White Frames | Coordinate: Preliminary quotation on frames Critical measurements Field measurements prior to order Estimated installation Frame installation Sign installation (VW clip only) | DCD Stage | 15 weeks |
| Plan B | Customer Area Furniture, Counters & Displays | Coordinate furniture order Preliminary quote Confirm order based on final construction plans Estimate installation | DCD Stage | 10-12 weeks |
| Savoia Canada, Olympia Tile, Centura | Showroom Tile | Coordinate tile order: Confirm preliminary material required and estimate installation. | DCD Stage | 6-8 weeks |
| Stone Tile, Olympia Tile or Savoia Canada | Wood-look Tile Floor and Concrete-look tiles | Coordinate Tile Flooring: Confirm preliminary material required Order from Stone Tile or Olympia Tile+Stone | DCD Stage | 6-8 weeks |
| Dealer Architect | Construction Drawings | Coordinate with Weis & Associates and suppliers to ensure appropriate corporate design directions and Volkswagen expectations. | 30%, 60%, 90% Dwg. review | 3 weeks per revision |
| G.C./ Project Manager | Coordinate finishes | Coordinate with Weis & Associates and suppliers to ensure appropriate implementation of finishes. | During construction | Ongoing |
| Safeguard Marketing Solutions | Interior Graphics (banners, wall art) | Coordinate with Weis & Associates and supplier to ensure appropriate implementation. | End of construction | 2 weeks |
| Safeguard Marketing Solutions or local supplier | Interior Secondary Signs (room, directional, etc.) | Coordinate with Weis & Associates and supplier to ensure appropriate implementation. | End of construction | locally |

 $^{^{*}}$ Please copy Weis & Associates on all communications for best possible assistance and guidance



Interior Finishes (



Customer-Facing Area Floor Finishes

PT-1

| | Showroom / Customer Area / NVD | | | | |
|-------|--------------------------------|----------------------------------|---------------|--|--|
| lmage | Supplier | Product | Specification | | |
| | Olympia | Casalgrande - Granitogres Boston | 24"x24" | | |
| | Savoia | Casalgrande - Granitogres Boston | 24"x24" | | |
| TEACH | Savoia | Fiandre - VW Light Grey - R10 | 24"x24" | | |
| | Centura | Munich Gray | 24"x24" | | |

PT-1 a

| Service Drive / Customer Washroom | | | |
|-----------------------------------|----------|-------------------------------------|---------------|
| lmage | Supplier | Product | Specification |
| | Olympia | Casalgrande Granito Arizona Secura | 12"x12" |
| | Olympia | Casalgrande Granito Arizona Secura | 8"x8" |
| | Olympia | Arkansas | 12"x12" |
| | Savoia | Casalgrande Granito Arizona Secura | 12"x12" |
| | Savoia | Casalgrande Boston R11 | 12"x12" |
| | Argelith | Light Grey R11 (Service Drive Only) | 12"x12" |

PT-2

| Service Drive Alternate | | | | |
|-------------------------|----------|-------------------------------|---------------|--|
| lmage | Supplier | Product | Specification | |
| | Olympia | Casalgrande VW New York - R10 | 12"x12" | |
| | Savoia | Casalgrande VW New York - R10 | 12"x12" | |

PT-3

| Workshop Drive Ailes and Workbays | | | |
|-----------------------------------|----------|-------------------------------------|---------------|
| lmage | Supplier | Product | Specification |
| | Olympia | Casalgrande Granito Arizona Secura | 12"x12" |
| | Olympia | Casalgrande Granito Arizona Secura | 8"x8" |
| | Olympia | Arkansas | 12"x12" |
| 为那 企业208 | Savoia | Casalgrande Granito Arizona Secura | 12"x12" |
| | Savoia | Casalgrande Boston R11 | 12"x12" |
| | Argelith | Light Grey R11 (Service Drive Only) | 12"x12" |



^{*}Alternate manufacturer must provide product of equal type and quality.

PT-4

| | Workshop Drive Ailes and Workbays (Used for demarcation only) | | | | | |
|-------|---|-------------------------------|-------|--|--|--|
| lmage | Image Supplier Product Specification | | | | | |
| | Olympia | VW Anthracite 08 - R11 Secura | 8"x8" | | | |
| | Savoia | VW Anthracite 08 - R11 Secura | 8″x8″ | | | |

Showroom Platforms / Offices / Write-up (Laid in staggered bond pattern parallel to front façade)

| Image | Supplier | Product | Specification |
|-------|---------------|----------------------------------|---------------|
| | Olympia | Havana Cherry; Porcelain Tile | 200x1200 mm |
| | Savoia | Havana Cherry; Porcelain Tile | 200x1200 mm |
| | Roca Tile USA | Roca Tile - Cherry Natural 8x48" | 8x48" |

CLT1

| Showroom Highlight Platform | | | | |
|-----------------------------|---------------|---------------------------------|--------------------|--|
| Image | Supplier | Product | Specification | |
| | Olympia | Casalgrande Padana Harlem | 24"x24" or 24"x48" | |
| 150000 | Savoia | Casalgrande Padana Harlem | 24"x24" | |
| - | Savoia | Fiandre - VW SHARP CORE SL R9 - | 24"x24" | |
| | Roca Tile USA | Basel Negro | 24"x24" | |



^{*}Alternate manufacturer must provide product of equal type and quality.

CT-1 / CT-2

| Washroom Wall Tiles | | | |
|---------------------|----------|---|-------------------------|
| Image | Supplier | Product | Specification |
| | Savoia | Light: Purity Ice | 8" x 16" (203 x 457 mm) |
| | Savoia | Dark: Purity Breeze | 8" x 16" (203 x 457 mm) |
| | Dal Tile | Light: Color Story Wall - American Olean Line. Designer White, Matte finish 0061 (1) | 4" x 12" |
| | Dal Tile | Dark: Color Story Wall - American Olean Line. Storm Grey, Matte finish 0040 (2) | 4" x 12" |
| | Olympia | Light: CDC Matte Arctic White | 4" x 16" |
| | Olympia | Dark: CDC Matte Sterling Grey | 4" x 16" |



^{*}Alternate manufacturer must provide product of equal type and quality.

| Interior Finishes | | Material Specification | | |
|-------------------|--|---|--|--|
| Product Photo | Key/Location | Product | Supplier | |
| | PTB Baseboard at Tiles (PTx) | Porcelain Tile base Colour to match floor colour; 100mm high. Alternate: Quartz Baseboard - White by Dal Tile; 100mm high. | All VW Approved Tile Suppliers | |
| | WDB Baseboard at Wood-look Tiles | MDF baseboard Square profile, 4" (102mm) height. Ultra Spec SCUFF-X paint recommended in high traffic areas. Paint colour "Chantily Lace" OC-65 | Dealer source Local Supplier | |
| | FT2 Transitions Strip Between PT and WD1a | Floor Transition strip Colour: Aluminum | Schlueter System Local Supplier | |
| | FT3 Stairs | Stair Nosing Colour: Grey | Schlueter System Local Supplier | |
| | CP-1 Service Workshop | Tinted Sealed Concrete Floor, hardened, colour to match RAL 9006. Alternate: Diamond Epoxy Coating. Local supplier. Alternate #2: Stonhard Stonshield HRI medium texture colour - driftwood, and carcoal epoxy coating. | Sika Colourplete with Sikafloor 3S, Stonhard or Local Supplier | |
| | CA Non-customer Facing Areas | Upstairs Carpet in roll sheets or modular carpet tile. Style 1: Tenera/ Trona Style 2: Metri/ Quartz | Tandus Centiva or Local Supplier | |
| | C1 Customer and Sales Area Ceiling | Acoustic Ceiling tiles Fineline 1/8" DXFF grid with Mars Clima plus tile 600 x 1200 mm or Silhouette 1/8 reveal grid with Ultima 9/16" beveled regular 600 x 1200 mm tile. Colour: white. | Armstrong Tiles or CGC | |

^{*}Alternate manufacturer must provide product of equal type and quality.



| Interior | Finishes | Material Specification | | |
|---------------|--|---|--|--|
| Product Photo | Key/Location | Product | Supplier | |
| | C2 Showroom Ceiling | Drywall Ceiling paint - Level 5 finish Colour RAL 7021; Dark grey, matt. or NCS S 8500-N | General Contractor | |
| | C3 Drywall Ceiling | Drywall Ceiling painted white. Colour: Chantilly Lace OC-65 | Benjamin Moore, or local supplier | |
| | P1 All Customer Facing Walls | Wall Paint Ultra Spec SCUFF-X paint recommended for high traffic areas. Colour: Chantilly Lace OC-65 | Benjamin Moore or Local Supplier | |
| | P2 Service Workshop Walls | Wall Paint Above 6' level of shop wall. Colour: Paper White 1590 | Benjamin Moore or Local Supplier | |
| | P3 Service Workshop Walls | Wall Paint Below 6' level of shop wall. Colour: Marina Grey 1599 | Benjamin Moore or Local Supplier | |
| | P4 Welcome Wall Blue | Benjamin Moore: Toronto Blue (2060-40) Sherwin Williams: Volskwagen Blue Behr: Yucatan (P490-5) | Benjamin Moore, Sherwin Williams, Berh or RAL 240 60 40 Safeguard | |
| | ID-1 Light Switch and Power Outlet Plates | White finish | Local Supplier | |

^{*}Alternate manufacturer must provide product of equal type and quality.



| Interior Finishes | | Material Specification | | |
|-------------------|--------------------------|---|--|--|
| Product Photo | Key/Location | Product | Supplier | |
| | ID-2 | Lever style; brushed aluminum finish | Local Supplier | |
| | Door Handles | | | |
| | WS1 Window Shade | Thermoveil 1300 Series Colour: Silver Birch 1319 | Mechoshade | |
| | FM1 Entry Mats | Winter Floor Mats Rubber-backed. Continuous lengths with minimal seams. Colour: Dark Grey | Local Supplier | |
| | FM2 | Floor Mat / Pedimat | Construction Specialties, Inc., Gridline | |
| | Vestibule & Entrances | Architectural, stainless steel grid, with high tech appearance. Rolling load tested to 500lbs | G6 or equal supplied locally | |
| The last | FM3 | Floor Mat / Pedimat | Construction | |
| | Vestibule & | Durable all aluminum rails for use outside. Anodized aluminum rails with exterior grade carpet in | Specialties, Inc., Pedimat | |
| | Entrances | 9325 Graphite colour | AA-M2 or equal supplied locally | |
| | FM4 | Floor Mat / Pedimat Architectural entrance grid with, carpet | Construction Specialties, Inc., | |
| | Vestibule & | inserts for additional debris removal. Metal satin | Treadline | |
| | Entrances | finished type 304 stainless steel and exterior grade carpet in 9325 Graphite colour | T1 or equal supplied locally | |
| | LAM-1 | Furniture Laminate Pfleiderer Decor: R42006 - HAVANNA CHERRY - matt | Pfleiderer - DUROPAL | |
| | Furniture | Note: Laminates can only be used for millwork elements approved by Weis or non-customer facing furniture. | | |

^{*}Alternate manufacturer must provide product of equal type and quality.



| Interior | Finishes | Material Specification | |
|---------------|-----------------|---|----------------------|
| Product Photo | Key/Location | Product | Supplier |
| | LAM-2 | Furniture Laminate Pfleiderer Decor: U11027 - ICY WHITE | Pfleiderer - DUROPAL |
| | Furniture | Note: Laminates can only be used for millwork elements approved by Weis or non-customer facing furniture. | |
| | LAM-3 Furniture | Furniture Laminate Pfleiderer Decor: U12215 - ANTHRACITE | Pfleiderer - DUROPAL |
| | | Note: Laminates can only be used for millwork elements approved by Weis or non-customer facing furniture. | |



^{*}Alternate manufacturer must provide product of equal type and quality.

Exterior Finishes



| Exterior Finishes | | Material Specification | | |
|-------------------|---|---|---|--|
| Product Photo | Key/Location | Product | Supplier | |
| | ST1 Building Perimeter / Landscaping | Decorative pebbles Washed river rocks in 2"- 4" diameter (50-100 mm) | Local supplier | |
| | PV1 Front of Main Entrance | Unit Paver Series 3000; (150 x 300 x 70 mm) Colour: Mineral Ice Grey | Unilock | |
| | PV2 Front of Main Entrance | Unit Paver Series 3000; (150 x 300 x 70 mm) Colour: Black Onyx *Used for demarcation only | Unilock | |
| | CW1 Curtain Wall Mullions | Curtain wall frame Anodized aluminum finish (50 x varied mm) Entry Doors to be Kawneer's 190 Narrow Stile Entrance | Kawneer 1600 SSG or equivalent | |
| | GL1 Front, Side Glazing | Clear, low iron, glare reduction, Low-E glass in showroom Frame: anodized aluminum finish (Size varies). Note: Double high performance glazing with low-E coating in the 3rd surface and argon fill is highly recommend for energy efficiency. | PPG Industries, AGNORA Glass or equivalent | |
| | GL2 Front, Side Glazing Spandrel Panel | Spandrel Glass Clear, low iron, exterior lite, cavity and 2nd laminated light with .060", Arctic Snow (68%) PVB interlayer. | PPG Industries AGNORA Glass or equivalent | |
| | OH1 Service Frame Doors | Aluminum Glazed OH door Clear anodized aluminum finish with full-glazed sections except bottom row (size varies) - Hormann 800-series OH door - Rytec Rigid Rolling Door - Spiral FV | Assa Abloy Doors Hormann Rytec Doors | |

^{*}Alternate manufacturer must provide product of equal type and quality.



| Exterior Finishes | | Material Specification | | |
|-------------------|--|--|--|--|
| Product Photo | Key/Location | Product | Supplier | |
| | OH2 Shop Entrance/ Exits | Insulated metal OH door Solid sections painted, third row full-glazed in aluminum frame (size varies) | Assa Abloy Doors Hormann Rytec | |
| | MC1 Side and Back Elevations | Metal cladding CL7040/CL840: Symmetrical 37" wide wall sheet with equally spaced 1 1/2" deep ribs 7/8" Corrugated: 2.66" from crest to crest Colour: RAL 9006 or closest match | Vicwest or equivalent | |
| | CB1 Exterior Above Doors and Openings | Concrete masonry unit (alternative) Smooth face ashlar; (100 x 400 x varied mm) Colour: Ivory | Richvale York Block Inc. or equivalent | |
| | CB2 Side Elevations | Concrete masonry unit (alternative) Smooth, face standard unit; (200 x 400 x varied mm) Colour: Arctic White ACM option ALUCOBOND - Cadet Grey - Gloss 15-25 (or similar) | Richvale York Block Inc. ALUCOBOND or equivalent | |
| | ACM1 White Frames | Aluminum Composite Material; Colour: White, finish 70% gloss | Alucobond Sobotec (exclusive supplier) | |
| A Dr. Section of | MP Rooftop, Mechanical Units | Showroom Roof Top Screening Colour to match exterior cladding RAL 9006 | Vicwest or equivalent | |
| | EP1 / EP2 Exterior Door Paint | Exterior Door Paint EP1 - Colour - "Iced Cube Silver" 2121-50 EP2 - Colour - "Chantilly Lace" OC-65 Note: Colour of doors must match the adjacent walls | Benjamin Moore | |

^{*}Alternate manufacturer must provide product of equal type and quality.



Lighting





New Lighting Elements

Light channel, suspended

Power track mounted spotlights

Lighting is very important to the overall White Frame scope, considering the new fixtures introduced with the NBD bring RGB colours that completely change the way the building interior is seen. See below example of typical Reflected Ceiling Plans, showing the basic lighting components (showroom pot lights, sales lighting, etc) and the new Light frame and panels over the highlight areas.



4000 K (LED)

4000 K (LED)

Overall Lighting Requirements

All areas of the dealership have specific requirements for lighting levels, colour temperature and CRI, which must be follow as per directions below. Consultants must also provide photometric calculations for review, to ensure required lighting is achieved. Engineering of lighting systems are performed by approved lighting suppliers in coordination with the Dealer's electrician.

Showroom

Fixture Style: Downlight with 40 and 60 degree distribution. Light Level: 850 lux average, 500 lux min.; 2:1 min/max

uniformity ratio

Colour Temperature: 4000K

CRI: min. 80

Customer Areas

Fixture Style: Down light with 55 degrees distribution

Light Level: min. 330 – 430 lux Colour Temperature: 4000K

Note: Match the Showroom colour temperature.

Offices

Fixture Style: Suspended linear fixture in combination with

down lights and/or wall wash. Light Level: min. 330 – 430 lux Colour Temperature: 4000K

Note: Match the Showroom colour temperature. Aim for

high-retail look.

New Vehicle Delivery

Fixture Style: RGB light frame with recessed multiples or

track lighting

Light Level: min 700 lux Colour Temperature: 4000K

Light Frames

Light Output: 2000 - 2200 lumen per linear metre

Colour Temperature: 4000K or RBG

(4" profile recommended)



Service Drive

Fixture Style: Suspended linear lighting fixture

Light Level: Average 750 lux

Colour Temperature: Range of 4000K

Note: Match the showroom colour temperature.

Welcome Wall

Fixture Style: Angled wall-wash. Light Level: 650 - 850 lux on wall Colour Temperature: Range of 4000K

Note: Match showroom colour temperature.

Item to be ordered through Safeguard VW Portal.



Showroom Lighting

LT-1a

Showroom - Recessed Adjustable Multiple LED Downlight. Dual head fixture. Black housing and trims; 4000K colour temp. CRI 90+.

Supplier Image Specification

Optecha Lighting

Product: Paris Downlights Euro Collection. EUR04 - PAR4 - Paris 4". Beam angle and lumen output to be based on mounting height and light level requirements. Color black.

CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: 1700lm/20W - 4 Inch or 2000lm/25W - 4 Inch.

Beam angle and lumen output to be based on mounting height and

light level requirements. Color black.

Product Code: PAR4-2-SQ-BL-BL-X-40K-90-20-V-UNV-NCS2

Beam Angle Reflector 15°

Mercury / Sistemalux - Iguzzini Product: BRIDGELUX VERO18 LED module, (LM-80 tested). Model: 8228 -Double

CRI:90

CCT (Color Temperature): 4000K

Lumens: 3281lm per lamp. High output, 28.5W. Beam angle and lumen output to be based on mounting height and light level

requirements. Color black.

Product Code: 8228-SPS016912-20

Beam Angle Reflector 15°

Richporter Lighting

Product: Clairage On Light. CARDA 7"x7" Led Downlight Fixture. Dual-head

Version

CRI: 90 min. value


CCT (Color Temperature): 4000K

Lumens: 3281lm per lamp. Beam angle and lumen output to be based on

mounting height and light level requirements. Color black.

Product Code: ON LIGHT 7"x7" (Required dual-head version)

Beam Angle Reflector 15°









LT-1b

Showroom - Recessed Adjustable Multiple LED Downlight. Dual head fixture. Black housing and trims; 4000K colour temp. CRI 90+.

Supplier **Image** Specification

Optecha Lighting

Product: Paris Downlights Euro Collection. EUR04 - PAR4 - Paris 4". Beam angle and lumen output to be based on mounting height and light level requirements

CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: 1700lm/20W - 4 Inch or 2000lm/25W - 4 Inch.

Beam angle and lumen output to be based on mounting height and

light level requirements. Color black.

Product Code: PAR4-2-SQ-BL-BL-X-40K-90-20-V-UNV-NCS2

Beam Angle Reflector 40°

Mercury / Sistemalux - Iguzzini

Product: BRIDGELUX VERO18 LED module, (LM-80 tested). 4000K: 90CRI Model: 8228 - Double. Finish black

CRI:80



Lumens: 3234lm per lamp. Beam angle and lumen output to be based on mounting height and light level requirements. Color black.

Product Code: 8228-SPS016912-40

Beam Angle Reflector Each optical assembly is adjustable 45° on all axes.

Richporter Lighting

Product: Clairage On Light. CARDA 7"x7" Led Downlight Fixture. Color Ral 9005 black


CRI: 90 min. value



Lumens: 5100 LM (34W). Beam angle and lumen output to be based on mounting height and light level requirements. Color black.


Product Code: ON LIGHT 7"x7" (Required dual-head version)

Beam Angle Reflector SP 36°









LT-1c

Showroom - Recessed Adjustable Multiple LED Downlight. Dual head fixture. Black housing and trims; 4000K colour temp. CRI 90+.

Supplier Image Specification

Description: Paris Downlights Euro Collection. EUR04 - PAR4 - Paris 4".

Optecha Lighting



CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: 1700lm/20W - 4 Inch or 2000lm/25W - 4 Inch.

Beam angle and lumen output to be based on mounting height and

light level requirements. Color black.

Product Code: PAR4-2-SQ-BL-BL-X-40K-90-20-V-UNV-NCS2

Beam Angle Reflector 60°

Mercury / Sistemalux - Iguzzini



Description: BRIDGELUX VERO18 LED module, (LM-80 tested). Custom to 4000K, 90CRI. Model: 8228-HO-490-60-UNV-02-SPS017554

CRI:80

CCT (Color Temperature): 4000K

Lumens: 3234lm per lamp. Beam angle and lumen output to be based on mounting height and light level requirements. Color black.

Product Code: 8228-HO-490-60-UNV-02-SPS017554

Beam Angle Reflector Wide Flood optic 60°. Each optical assembly is adjustable 45° on all axes.

Richporter Lighting



Description: Clairage On Light. CARDA 7"x7" Led Downlight Fixture. 2S Double Square. Color RAL 9005 Black

CRI:90

CCT (Color Temperature): 4000K

Lumens: 5100 LM (34W). Beam angle and lumen output to be based on mounting height and light level requirements. Color black.

Product Code: ON LIGHT 7"x7" (Required dual-head version)

Beam Angle Reflector 60°



^{*}Alternate manufacturer must provide product of equal type and quality.

LT-1d

Showroom Track Lights / NVD Room - LED Track Head. Black housing; 360° horizontal coverage and 90° vertical; 4000K colour temp.

Supplier

Image

Specification

Optecha Lighting



Description: TRAC-LITES™ 21W LED CYLINDER R610L SERIES. LED Track Head Black Housing 360 deg horizontal coverage and 90 deg vertical.

CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output is to be based on mounting height and light level requirement.

Product Code: R610L-40K-90CRI-OFF-X-X

Mercury / Sistemalux - Iguzzini



Description: Studio Projector LED. BRIDGELUX VERO LED MODULE. Color matte

black

CRI:80

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: 1770S1-BO-*940-50-120-52 *Code and lighting information may vary depending on the configuration

Richporter Lighting



Description: Clairage On Light. Bit BMT 3" LED TRACK LIGHT. Color RAL 9005

Black

CRI:90

CCT (Color Temperature): 4000K

Lumens: 2000 LM (14W)196LM/W. Lumen output to be based on mounting height and light level requirements.

Product Code: ON LIGHT Bit 40-40-90



^{*}Alternate manufacturer must provide product of equal type and quality.

LT-2a

Suspended RGB Light Frame Dark grey RAL 7021 housing, matte. RGB LED variable, 4000K. 4" profile with fabric diffusers. Controllers to be coordinated with Supplier; minimum requirement is a simple wall mounted RGB colour slider.

Supplier Image Specification

Optecha Lighting

Description: Suspended Light Frame. Dark grey RAL 7021 housing, RGB LED. Custom size and mounting

CRI:90

CCT (Color Temperature): RGB

Lumens/Watts: Lumen output to be based on mounting height and light level requirements

Description: Sistemalux Canale Pendant. 8605 - Down. RGB LED Strip.

Product Code: HPL-RGB-DMX-120-(SIZE)

Mercury / Sistemalux - Iguzzini

CRI: 90

CCT (Color Temperature): RGB

Lumens: 4000K. Lumen output to be based on mounting height and light level requirements.

Product Code: 8605-SPS017043

Richporter Lighting

Description: Media Graph TLS. Lumi Cloud Bespoke Aurora. Black

CRI:>90

CCT (Color Temperature): RGB

Lumens: Efficiency: 64.8 lm/w- (power consumption depends on fixture configuration). Lumen output to be based on mounting height and light level requirements.

Product Code: TLS AURORA(RGBW) LUMICLOUD - TLS-LC-BE-AU- RC-WxL-65K-CL-SP-FS-CF-LF-DMXT-P-IN. *Code and lighting information may vary depending on the configuration







LT-2b

Suspended RGB Light Frame Dark grey RAL 7021 housing, matt. RGB LED variable. 4" profile with fabric diffusers. Controllers to be coordinated with Supplier; minimum requirement is a simple wall mounted RGB colour slider.

Supplier Image Specification

Optecha Lighting



Description: Suspended Light Frame. Dark grey RAL 7021 housing, RGB LED 1400W

CRI:90

CCT (Color Temperature): RGB

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: HPL-RGB-DMX-120-(SIZE)

Mercury / Sistemalux - Iguzzini



Description: Led Panel Pendant. RGB LED pendant fixture. Gray painted finish. 02 - Black RAL7021

CRI: 90

CCT (Color Temperature): RGB

Lumens: R 4508lm G 10626lm B 3864lm per panel. Lumen output to be based on mounting height and light level requirements.

Product Code: 8888-SPS015082

Richporter Lighting



Description: Media Graph TLS. Lumi Cloud Bespoke Aurora. Black

CRI:>90

CCT (Color Temperature): RGB

Lumens: Efficiency: 64.8 lm/w- (power consumption depends on fixture configuration). Lumen output to be based on mounting height and light level requirements.

Product Code:TLS AURORA(RGBW) LUMICLOUD - TLS-LC-BE-AU- RC-WxL-65K-CL-SP-SQ-CF-LF-DMXT-P-IN. *Code and lighting information may vary depending on the configuration



^{*}Alternate manufacturer must provide product of equal type and quality.

LT-2c

Customer Lounge Optional Light Frame - White LED

Supplier

Image

Specification

Optecha Lighting



эреспісано

CRI:90

CCT (Color Temperature): RGB 4000K


Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Description: Suspended Light Frame. Dark grey RAL 7021 housing, RGB LED

Product Code: HPL-RGB-DMX-120-(SIZE)

Description: Sistemalux Canale Pendant. 8605 - Down. RGB LED Strip.

Mercury / Sistemalux - Iguzzini




CRI:90

CCT (Color Temperature): RGB

Lumens: 4000K. Lumen output to be based on mounting height and light level requirements.

Product Code: 8605-SPS017043

Richporter Lighting



Description: Media Graph TLS. Lumi Cloud Bespoke Aurora. Black

CRI:>90

CCT (Color Temperature): RGB

Lumens: Efficiency: 1072.3 lm/sqf.* Lm/sqf are calculated at LED source.

Lumen output to be based on mounting height and light level requirements.

Product Code: TLS ASTRA LUMILINE - TLS-LC-BE-AS-RC-WxL-40K- CL-SP-FS-CF-LF-0-10- P-IN



^{*}Alternate manufacturer must provide product of equal type and quality.

Customer Zone Lighting

LT-3

Customer Areas & Office Light - Recessed LED downlight with standard distribution and white trim.

Supplier

Image

Specification

Optecha Lighting

Description: Recessed Wall Wash Downlight. Recessed LED round adjustable downlight with white trim finish. Acuity

CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: LBR6-X-4000K-AR-TRW-LSS-X-X-UGZ

Mercury / Current Lighting **Description:** 6RD 6" Round Downlight. DWT Diffuse Clear Anodized with White Flange

CRI:90

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: LBRP-M LS ML CS9 LBRP 6RD T DWT LB-6R-F-TG

Richporter Lighting

Description: Lightolier by signify. Downlighting. Calculite LED 6" gen 3. C6RDL Round Downlight. White Matte


CRI:80

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: Signify C6RDL







LT-3a

Customer Areas & Office Light - LED wall wash downlight with alzak reflector finish and white trim.

Supplier

Image

Specification

Optecha Lighting

Description: Onelux - Recessed Wall Wash Downlight. Recessed LED round adjustable downlight with white trim finish

CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: MUR5-AD-R-WH-CS-55D-40K-90-20-V-UNV-NCR1

Mercury / Current Lighting **Description:** 6RD 6" Round Downlight. DWT Diffuse Clear Anodized with White Flange

CRI:90

CCT (Color Temperature): 120-347V auto sensing, lumen and CCT selectable. Lumen output to be based on mounting height and light level requirements.

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: LBRP-M LS ML CS9 LBRP 6RD T DWT LB-6R-F-TG

Description: Lightolier by signify. Downlighting. Calculite LED 6" gen 3. C6RWW

Round Wall Wash. White Matte

CRI:80

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: Signify C6RWW Round Wall Wash

Richporter Lighting





^{*}Alternate manufacturer must provide product of equal type and quality.

Welcome Wall Washer - Laser Blade Large Wall Washer (for non-illuminated Welcome Walls only) Black housing and trim; 23W white LED; 40° swing-out; 4000K colour tem. CRI 90.

Supplier

Image

Specification

Optecha Lighting

Description: Onelux. Laser Blade Wall Washer. Black Housing and trim, 18W white LED, wall washer optic

CRI:90

CCT (Color Temperature): 3000K

Lumens/Watts: 750lm/10W/5 Cell 1350lm/18W/10 Cell.

Description: iGuzzini CL R2 Laser Blade Large Wall Washer

Lumen output to be based on mounting height and light level

requirements.

Product Code: VEG-10-30K-WW-UNV-90-B

Mercury /

Sistemalux - Iguzzini

CRI:80

CCT (Color Temperature): 4000K

 $\textbf{Lumens:} Lumen \ output \ to \ be \ based \ on \ mounting \ height \ and \ light \ level$

requirements.

Product Code: I.LB L2 TR 840 WW 120

Richporter Lighting

Description: Clairage On Light. BK RAL 9005 black **CRI:** 90

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level

requirements.

Product Code: LWL 40 90 WW BK

B








New Vehicle Delivery Suspended Light Frame - White LED

Supplier

Image

Specification

Optecha Lighting



Description: Suspended Light Frame. Dark grey RAL 7021 housing. Design using a single frame

CRI: 90


CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: HPL-40000K-120-(SIZE)

Description: Sistemalux Canale Pendant. 8605 - Down. RGB LED Strip.

Mercury / Sistemalux - Iguzzini




CRI:90

CCT (Color Temperature): RGB

Lumens: 4000K. Lumen output to be based on mounting height and light level requirements.

Product Code: 8605-F UNV Custom RAL finish RAL7021. Rectangular Configuration with size to be confirmed

Richporter Lighting



Description: Ceiling Mounted or Suspended Light Frame, 4" Black

CRI:>90

CCT (Color Temperature): 4000K.

Lumens: Efficiency: 100.0 Lm/W. Lumen output to be based on mounting height and light level requirements.

Product Code: TLS ASTRA LUMILINE




^{*}Alternate manufacturer must provide product of equal type and quality.

NVD / Reception / Sales Areas - Pendant Mounted LED downlight with direct distribution and matte white finish.

Supplier Image Specification

Optecha Lighting



Description: Acuity - Linear Suspended Lighting. Pendant Mounted LED Linear Downlight with direct distribution and matte white finish. Mark Architectural Lighting SLOT 2 Pendant Direct

CRI:80

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: S2PD-X-80CRI-40K-X-WHT-ZT

Mercury / Current Lighting



Description: Prescolite. LITECONTROL 4L-P-D or 2L-P-D MOD 3 LED Pendant Direct

CRI: 90

CCT (Color Temperature): CCT selectable

Lumens: Lumen selectable. Lumen output to be based on mounting height and light level requirements.

Product Code: 4L PD SOF C1 40K D050 1C UNV or 2L PD SOF C1 40K D050 1C

Description: 2L-P-D MOD 3 LED Pendant Direct

CRI:90

CCT (Color Temperature): CCT selectable

Lumens: Lumen selectable. Lumen output to be based on mounting height and light level requirements.

Product Code: 2L PD SOF C1 40K D050 1C UNV

Richporter Lighting



Description: VISIONEERING LMEZ 3 LED Suspended Linear Direct/Indirect Luminaire

CRI:80

CCT (Color Temperature): 4000K

Lumens: 1000 lm/ft. Lumen output to be based on mounting height and light level requirements.

Product Code: LMEZ3-P96-LED840K10LFUNV-C91




^{*}Alternate manufacturer must provide product of equal type and quality.

LT-6a

Service / Reception / Sales Offices - Pendant Mounted LED downlight with direct/indirect distribution and matte white finish.

Supplier Image

Optecha Lighting



Description: Linear Suspended Lighting. Pendant Mounted LED Linear Downlight with direct distribution and matte white finish

Specification

CRI:90

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements

Product Code: S2LD-X-80CRI-40K-X-WHT-ZT

Mercury / Current Lighting



Description: LITECONTROL 6L-P ID MOD 6 LED Pendant Indirect/Direct

CRI:90

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: 4L P ID SOF C1 40K I030 D050 1C UNV or 2L P ID

Description: VISIONEERING LMEZ 3 LED Suspended Linear Direct/Indirect

Luminaire

CRI:80

CCT (Color Temperature): 4000K

 $\textbf{Lumens:} 1000 \ \text{Im/ft.} \ \text{Lumen output to be based on mounting height and}$

light level requirements.

Product Code: LMEZ3-T96-LED840K06/10LFUNV-C91

Richporter Lighting





^{*}Alternate manufacturer must provide product of equal type and quality.

Meeting Room - Suspended LED downlight direct / indirect distribution with matte white finish.

Supplier

Image

Specification

Optecha Lighting



Description: Linear Suspended Lighting DI. Suspended LED Downlight direct / indirect distribution with matte white finish. Mark Architectural Lighting PLANAR

I/D OR DIRECT PENDANT TUNABLE WHITE

CRI:80

CCT (Color Temperature): 4000K

Lumens/Watts: Up to 140lm/w.

Lumen output to be based on mounting height and light level requirements.

Product Code: GRD-LLP-X-80CRI-40K-ID1000LMF-20/80-MIN1-ZT-120-SCT-

24A-C210

Mercury / Current Lighting



Description: LITECONNTROL SAE 103 LED Pendant Indirect/Direct

CRI:90

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: SAE103 PID LPA SGL C1 40K D01 1C UNV

Description: Visioneering Allura M (Moda)

CRI:80

CCT (Color Temperature): 4000K

 $\textbf{Lumens:} \ 120 \text{L} - 12000. \ \textbf{Lumen output to be based on mounting height and}$

light level requirements.

Product Code: ALR-M96-LED840K120LUNV-F09

Richporter Lighting





^{*}Alternate manufacturer must provide product of equal type and quality.

Washroom Wall Wash - Surface/Wall mounted LED downlight with matte white finish.

Supplier

Image

Specification

Optecha Lighting



Description: Acuity. Surface Wall Mounted LED Downlight with matte finish

CRI:80

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Description: LITECONTROL 4L-W-D MOD 3 LED Wall Direct or 2L WD

Product Code: S2LWD-LCB-X-80CRI-40K-X-WHT-ZT

Mercury / Current Lighting



CRI:90 CCT (Color Temperature): 4000K

> Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: 4L WD SOF C1 40K D01 1C UNV or 2L WD

Richporter Lighting



Description: Visioneering LMEZ LED Linear Luminaire

CRI:80+

CCT (Color Temperature): 4000K

Lumens: 100L - 10000

Product Code: LMEZ-W96-LED840K100LUNV-P04-M02



^{*}Alternate manufacturer must provide product of equal type and quality.

| ı | ٦ | Γ_ | Q |
|---|-----|----|---|
| - | - 1 | | 7 |

Shop - Service Department - LED high performance high bay fixture.

Supplier

Image

Specification

Optecha Lighting

Description: LHB Series LED High Performance Linear Highbay

CRI:>70

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level

requirements.

Product Code: LHB Series LHB-150LED-40K-120M-V-D or LHB Series LHB-

Description: Columbia Lighting PEL Peloton High Performance High Bay

150LED-40K-347-V-D

Mercury / Current Lighting

CRI:>80

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: ECH1 840 DW EDU PM

Description: Columbia Lighting PELA Linear High Bay

CRI:80

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: PELA 840 LXX B ED ST F5C006 93302310

Richporter Lighting



Description: Visioneering LHBC LED - Commercial-Grade Heigh or Low Bay Luminaire

CRI:80+

CCT (Color Temperature): 4000K

Lumens: 240L - 24000. Lumen output to be based on mounting height and

light level requirements.

Product Code: LHBC248-LED840240LUNV-P73



^{*}Alternate manufacturer must provide product of equal type and quality.

LT-9a

Service Department - LED 8ft long, suspended 10-12ft of the floor.

Supplier

Image

Specification

Optecha Lighting



Specification

CRI:80

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Description: LITECONTROL 6L-P-D MOD 3 LED Pendant Direct

Description: Strip Light. LED Striplight 4 or 8ft long, mounted 10-12ft high

Product Code: CLX-X-SEF-WDL-40K-80CRI-WH

Mercury / Current Lighting



CRI:90

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: 6L PD SOF C1 40K D01 1C UNV

Richporter Lighting



Description: Visioneering LCOM LED - Commercial Strip Luminaire

CRI:80+

CCT (Color Temperature): 4000K

Lumens: 140L - 14000. Lumen output to be based on mounting height and light level requirements.

Product Code: LCOM-96-LED-840K140L-P77



^{*}Alternate manufacturer must provide product of equal type and quality.

| | | LT-10a |
|-------------------|-------|---|
| | Gen | eral Purpose LED - Suspended LED with white finish. |
| Supplier | lmage | Specification |
| Optecha Lighting | | Description: Surface LED Wrap. White finish, 4' long. |
| | | CRI: 80 |
| | 7 | CCT (Color Temperature): 4000K |
| | | Lumens/Watts: 4000lm. Lumen output to be based on mounting height and light |
| | | level requirements. |
| | | Product Code: VT Series |
| Mercury / Current | | Description: Columbia Lighting CSL Striplight |
| Lighting | 802 | |
| | | CRI:90 |
| | | CCT (Color Temperature): CCT selectable |
| | | Lumens: 120-347V auto-sensing, lumen selectable. Lumen output to be |
| | | based on mounting height and light level requirements. |

Richporter Lighting



Description: Visioneering LMNE-Magic Neutron Industrial/Commercial Lighting

CRI:80+

Product Code: CSL4-A-LSCS

CCT (Color Temperature): 4000K

Lumens: 040L - 4000. Lumen output to be based on mounting height and

light level requirements.

Product Code: LMNE-48-LED-40K040LUNV



^{*}Alternate manufacturer must provide product of equal type and quality.

LT-10b

Wash Bay (wet area) Enclosed and Gasketed LED with white finish.

Supplier

Image

Specification

Optecha Lighting

Description: Vapor Tite LED. Enclosed and Gasketed, 4' or 8'.

CRI:80

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level

requirements.

Product Code: VT Series

Mercury / Current Lighting **Description:** Columbia Lighting LXEM

CRI:80

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: LXEM4 40 RFA EDU

Richporter Lighting

Description: CERTOLUX CRV LED - Cleanroom Ceiling - Vapour Tight

CRI:80+

CCT (Color Temperature): 4000K

Lumens: 200L - 20000. Lumen output to be based on mounting height and

light level requirements.

Product Code: CRV-96-LED840K200LUNV-C16-P78



^{*}Alternate manufacturer must provide product of equal type and quality.

LT-11a

Service / Parts Department - Surface mounted/suspended LED striplight with white finish.

Supplier

Image

Specification

Optecha Lighting

Description: Strip LED. White finish, 4' or 8' long, suspended or surface mounted 10-12ft high.

CRI:80

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: CLX-X-SEF-WDL-40K-80CRI-WH

Mercury / Current

Description: Columbia Lighting CSL Striplight

Lighting

CRI:90

CCT (Color Temperature): Switchable CCT, 3500/4000/5000K

Lumens: 120-347V auto-sensing, lumen selectable. Lumen output to be based on mounting height and light level requirements.

Product Code: CSL4-A-LSCS

Richporter Lighting

Description: Visioneering LCOMLED - Commercial Strip Luminaire

CRI:80+


CCT (Color Temperature): 4000K

Lumens: 140L - 14000. Lumen output to be based on mounting height and

light level requirements.

Product Code: LCOM-96-LED-840K140L-P77







General Purpose Square Potlight - Recessed LED square downlight with white trim finish.

Supplier

Image

Specification

Optecha Lighting

Description: Dallas Downlight Recessed Downlight Recessed LED square downlight with white trim finish

CRI:90

CCT (Color Temperature): 3000K, 4000K, 5000K Selectable

Lumens/Watts: 600lm/8W. Lumen output to be based on mounting height and light level requirements.

Product Code: DAL4-SQ-OCC-M-120-90-W-NCS1

Mercury / Current Lighting **Description:** General Purpose Square Prescolite LBRP-SQD (120–347V) PRO CANLESS DIRECT INSTALL DOWNLIGHT

CRI:90

CCT (Color Temperature): CCT selectable

Lumens: 120-347V auto-sensing, CCT selectable. Lumen output to be based on mounting height and light level requirements.

Product Code: LBRP-M LS ML CS9 34 LBRP 6SQ T DWT LFR 6SQ H

Richporter Lighting

Description: Lightolier by Signify - Downlighting LyteProfile P6S 6" Square Downlight & Wall Wash

CRI:80

CCT (Color Temperature): 1000lm

Lumens: 4000K. Lumen output to be based on mounting height and light level requirements.

Product Code: 6SN / P6SDL20840-Z10U



^{*}Alternate manufacturer must provide product of equal type and quality.

| | _ | 4 | - |
|---|-----|---|-----|
| L | I - | 1 | . 3 |

Vestibule - Recessed LED round downlight with white trim finish.

Supplier

Image

Specification

Optecha Lighting

Description: Recessed Downlight Recessed LED round downlight with white trim finish

CRI:80 (90 Optional)

CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: LBR6-X-4000K-AR-TRW-LSS-X-X-UGZ

Mercury / Current Lighting



CRI:90

CCT (Color Temperature): CCT selectable

Lumens: 120-347V auto-sensing, lumen selectable. Lumen output to be based on mounting height and light level requirements.

Description: Prescolite LBRP-RD PRO CANLESS DIRECT INSTALL DOWNLIGHT

Product Code: LBRP-M LS ML CS9 LBRP 6RD T DWT LB-6R-F-TG

Richporter Lighting



Description: Ligholier by Signify Downlighting LyteProfile P6R 6" Round Downlight & Wall Wash

CRI:80

CCT (Color Temperature): 4000K

Lumens: 2500 lm. Lumen output to be based on mounting height and light level requirements.

Product Code: 6RN / P6RDL15840-Z10U



^{*}Alternate manufacturer must provide product of equal type and quality.

| 17 | Γ-1 | ıз | a |
|----|-----|----|---|
| _ | | LJ | a |

Vestibule Alternative Recessed 2" downlight for low clearance height.

Supplier

Image

Specification

Optecha Lighting

Description: Recessed LED 2" Downlight. White trim finish.

CRI:90



CCT (Color Temperature): 4000k

Lumens/Watts:600lm

Product Code: DAL2-RD-CCT-M-120-90-W

Description: Prescolite D2LED OPEN 2" LED OPEN DOWNLIGHT 120/277V

Mercury / Current Lighting

Richporter Lighting



CRI:80+

CCT (Color Temperature): 4000K

Lumens: Lumen package and configuration to suit project

Product Code: D2LED 2D9LED 15L

Description: Lightolier by Signify Downlighting Calculite 2" C2DL Downlight

White 2" round

CRI:90



CCT (Color Temperature): 4000K

Lumens: 1500 Im

Product Code: C2RDL15-9 -40FL-C2R-DL



^{*}Alternate manufacturer must provide product of equal type and quality.

Equipment / Exterior Lighting

| | | Equipment / Exterior Lighting |
|-------------------------------|-------|---|
| | | LT-17 |
| | | Cabinets - Under cabinet LED strip. |
| Supplier | Image | Specification |
| Optecha Lighting | | Description: Surface Mount Under Cabinet LED Linear. Aluminum extrusion with frosted lens. Custom sizes and output based on site conditions. |
| | - | CRI: 90 |
| | | CCT (Color Temperature): 4000K |
| | / | Lumens/Watts: Lumen output to be based on mounting height and light level requirements. |
| | 4 | Product Code: BAR Series |
| Mercury / Current Lighting | | Description: Columbia Lighting CUC Undercabinet |
| | | CRI: 90 |
| | | CCT (Color Temperature): Switchable CCT technology: 3000/3500/4000K |
| | | Lumens: Lumen output to be based on mounting height and light level requirements. |
| | | Product Code: CUC2-CS-ED120 |
| Richporter Lighting | | Description: Day-Brite CFI Linear LINCS LED undercabinet 19" Driver DIM |
| | | CRI: 90 |
| | | CCT (Color Temperature): 3000K |
| | | Lumens: Lumen output to be based on mounting height and light level requirements. |
| | | Product Code: LINCS100E-930WHG-DIM |



^{*}Alternate manufacturer must provide product of equal type and quality.

| EX | | | | |
|---------------------|-----------------|---|--|--|
| | Exit Public Are | as Running man - Edge-lit exit sign with LED light source. | | |
| Supplier | lmage | Specification | | |
| Optecha Lighting | | Description: Exit Running Man Edgelit LED.Finished in white. Universal mount with site-installed pictogram inserts | | |
| | 41 | Product Code: EDGRM | | |
| Mercury Lighting | | Description: Stanpro | | |
| | | Product Code: RMEA EDGELIT Universal Mounting | | |
| Richporter Lighting | | Description: BeLuce CURVA RM Surface / Recessed Edge-Lit Running Man | | |
| | ← 🏗 | Product Code: CRV-RM-L-S-BA | | |

| EM | | | |
|---------------------|---------------|---|--|
| | Emergency Lig | ghts - Commercial emergency light as required by code. | |
| Supplier | lmage | Specification | |
| Optecha Lighting | | Description: Emergency LED Light. Finished in white. Wall and ceiling mount. 120-347V input 1100 lumens | |
| | | Product Code: EDGRM | |
| Mercury Lighting | | Description: Stanpro | |
| | | Product Code: VN4-L GEN 2 | |
| Richporter Lighting | | Description: Beluce TEMPESTATM LED REMOTE 17W Wet Location LED Remote | |
| | | Product Code: TA-RMT-LED | |



^{*}Alternate manufacturer must provide product of equal type and quality.

ELT-1a

Front Lot Display - Large Viper LED, outdoor area light with grey smooth finish.

Supplier

Image

Specification

Optecha Lighting

Description: Area Post Mount LED. Finished in grey or white. Straight square steel pole, suitable EPA based on location.

CRI:80



CCT (Color Temperature): 4000K

Lumens/Watts: Lumen output to be based on mounting height and light level requirements.

Product Code: RSX or DSX

oddet code: Nox or box

Description: Beacon / VP3 Viper Area/Site

Mercury / Current Lighting

CRI: 70

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Description: Gardco by Signify Site Area EcoForm ECF-L large area luminaire

Product Code: VP3 4K7 UNV ASQU LGS

Richporter Lighting

CRI: 70

CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Product Code: ECF-L NW-G2 AR MGY

ELT-1b

| Front Lot Dis | play - Sc | guare straig | tht steel | pole with | grev tinis | h. |
|---------------|-----------|--------------|-----------|-----------|------------|----|
| | | | | | | |

Supplier Image

Specification

Mercury / Current Lighting

V

Description: HUBBELL Outdoor Lighting SSS-H Series Poles

Product Code: SSS POLE TO SUIT CONFIGURATION

Richporter Lighting

ı

Description: Gardco by Signify Ples & Brackets Site and Area Poles. Straight Square Steel

Product Code: SSS-CB



^{*}Alternate manufacturer must provide product of equal type and quality.

| ELT-2b Wall Lights - Small viper outdoor LED area light with grey smooth finish. | | | | | |
|---|--|----------|--|--|--|
| | | | | | |
| Optecha Lighting | Description: Wall Mount LED. Finished in grey or white. | | | | |
| | CRI:80 | | | | |
| | CCT (Color Temperature): 4000K | | | | |
| | Lumens/Watts: Lumen output to be based on mounting height and ligh | nt level | | | |
| | requirements. | | | | |
| | Product Code: WDGE2 LED Series | | | | |
| Mercury / Current | Description: Beacon / VP2 VIPER Area/Site | | | | |
| -ighting | | | | | |
| | Lumens: Lumen package and configuration to suit project | | | | |
| | Product Code: VP2 4K7 UNV WB LGS | | | | |
| | Description: Hubbell Outdoor Lighting RATIO Wall / RAR2 | | | | |
| | Lumens: Lumen output to be based on mounting height and light | nt level | | | |
| | requirements. | | | | |

Product Code: RWL2 4K7 UNV LGS

Richporter Lighting



CCT (Color Temperature): 4000K

Lumens: Lumen output to be based on mounting height and light level requirements.

Description: Gardco by Signify Site Area EcoFrom ECF-S Small area light

Product Code: ECF-S-32L-700-NW-G2-AR-3-UNV-MGY



^{*}Alternate manufacturer must provide product of equal type and quality.

| | ELT-3 |
|-------|---|
| | Bollards - Round/Square LED Bollard with grey finish. |
| Image | Specification |

Optecha Lighting

Supplier



Description: Bollard LED. Finished in grey or white.

Product Code: DSXB

Mercury / Current Lighting



Description: Hubbell Outdoor / Fresno Temple Series

Product Code: TMS/TMR 24LU 4K

ĮΝ

Description: Kim Lighting / Pavillion Impact Rated

Product Code: PA7R

Richporter Lighting



Description: Gardco by Signify Bollard Dome/bevel top louver

Product Code: 42 NW-G2 MGY



^{*}Alternate manufacturer must provide product of equal type and quality.